


WJ15EDGBG-3.5

PLUG-IN TERMINAL BLOCK

Download date : 2025-12-06



PCB connector

Rated current: 8 A

Rated voltage: 300 V

Pitch: 3.5 mm

Mounting: Wave soldering



For reference only!version1.0

UL/CUL

Use Group	B	C	D
Rate Voltage [V]	300	-	300
Rated Current [A]	8	-	8
Wire Range [AWG]	/		
Dielectric Voltage-Withstand	1.6KV		

IEC

Overvoltage Category	III	III	II
Contamination Class	3	2	2
Rated Voltage [V]	160	160	320
Rated Current [A]	8	8	8
Impulse withstand voltage [KV]	2.5	2.5	2.5
Conductor cross section[solid/flexible] [mm²]	/		

Material

Insulation Material	PA66
---------------------	------

WJ15EDGBG-3.5
PLUG-IN TERMINAL BLOCK

Download date : 2025-12-06




Flame retardant rating	UL94V-0
Conductor Material	Copper alloy
Plating of conductor surface	Sn plated

Other Data

Pitch/Poles [mm]/[P]	3.5/2-24
Stripping Length [mm]	/
Screw/Torque(Max)[N.m]	/
Operating temperature [°C]	-40~+105
Soldering temperature	260°C/5S
Pin dimensions [mm]	0.6*1.0
PCB Hole Diameter [mm]	Ø1.4

Dimensions

PCB opening diagram




Accessories

WJ15EDGBG-3.5

PLUG-IN TERMINAL BLOCK

Download date : 2025-12-06



[WJ15EDGKNRG-3.5](#)