




电路图：



目录仅供参考，实际规格依产品工程图为准 版本1.0

技术参数-UL ( 1059 )

| 等级 Use Group             | B       | C | D |
|--------------------------|---------|---|---|
| 额定电压 Rated Voltage [V]   | /       | / | / |
| 额定电流 Rated Current [A]   | /       | / | / |
| 耐电压 Withstanding Voltage | /       |   |   |
| 接线范围 Wire Range          | 24-8AWG |   |   |

技术参数-IEC(60947-7-2)

|                                  |     |
|----------------------------------|-----|
| 过电压类别 Overvoltage Category       | III |
| 污染等级 Contamination Class         | 3   |
| 额定电压 Rated Voltage               | /   |
| 额定电流 Rated Current               | /   |
| 额定冲击电压 Impulse withstand voltage | 8KV |

导线截面积 Conductor cross section

|                                |                         |
|--------------------------------|-------------------------|
| 单芯 Solid                       | 0.2-10.0mm <sup>2</sup> |
| 柔性导线 Flexible                  | 0.2-6.0mm <sup>2</sup>  |
| 柔性导线带冷压头 Flexible with ferrule | 0.25-6.0mm <sup>2</sup> |


材料 Material

|                                     |              |
|-------------------------------------|--------------|
| 绝缘材料 Insulation Material            | PA66         |
| 阻燃等级 Flame relardant rating         | UL94V-0      |
| 导体材料 Conductor Material             | Copper alloy |
| 导体表面镀层 Plating of conductor surface | Sn plated    |


一般参数 Other Data

|                                    |               |
|------------------------------------|---------------|
| 长/高/厚 Length/Height/Thickness [mm] | 90.5/42.6/8.2 |
| 连接点数 Connection Points             | 3             |
| 剥线长度 Stripping Length [mm]         | 12            |
| 导轨类型 Type of rail                  | DIN 35        |
| 螺丝/扭矩 Screw/Torque(Max)[N.m]       | /             |
| 工作温度 Operating temperature [°C]    | -40~+105      |

尺寸图



配件




FUVA6-XX




MUV6-10



PUV6-56



EB-35



EW-35



DGL2-35x7.5A



DGL2-35x7.5B



DGL2-35x7.5C




DGL2-35x7.5D



DUS6-103



DGS1-35x7.5W4.2x12



DGS1-35x7.5W5.2x15



DGS1-35x7.5W