



目录仅供参考，实际规格依产品工程图为准 版本1.0

技术数据-UL/CUL

等级 Use Group	B	C	D
额定电压 Rate Voltage [V]	600	600	600
额定电流 Rated Current [A]	85	85	5
接线范围 Wire Range [AWG]	26-4		
耐电压 Dielectric Voltage-Withstand	2.2KV		

技术参数-IEC


过电压类别 Overvoltage Category	III	III	II
污染等级 Contamination Class	3	2	2
额定电压 Rated Voltage [V]	800	1000	1000
额定电流 Rated Current [A]	76	76	76
额定冲击电压 Impulse withstand voltage [KV]	8	8	8
导线截面积[硬/柔] Conductor cross section [mm ²]	0.2-16.0		

材料 Material

绝缘材料 Insulation Material	PBT
阻燃等级 Flame relardant rating	UL94V-0

导体材料 Conductor Material	Copper alloy
导体表面镀层 Plating of conductor surface	Sn plated
一般参数 Other Data	
间距/极数 Pitch/Poles [mm]/[P]	20.0/2-12
剥线长度 Stripping Length [mm]	16
螺丝/扭矩 Screw/Torque(Max)[N.m]	M6/2.5
工作温度 Operating temperature [°C]	-30°C~+120°C
焊锡温度 Soldering temperature	260°C/5S
引针尺寸 Pin dimensions [mm]	2.0*10.0
PCB板孔径 PCB Hole Diameter [mm]	2.4*10.4

尺寸图



PCB开孔图

