

插拔式连接器
额定电流: 8 A
额定电压: 300 V
使用线径: 24-16 AWG
间距: 3.5 mm/3.81 mm
接线方式: 直插式弹簧连接



目录仅供参考，实际规格依产品工程图为准 版本1.0

技术数据-UL/CUL

等级 Use Group	B	C	D
额定电压 Rate Voltage [V]	300	-	300
额定电流 Rated Current [A]	8	-	8
接线范围 Wire Range [AWG]	24~16		
耐电压 Dielectric Voltage-Withstand	1.6KV		

技术参数-IEC

过电压类别 Overvoltage Category	III	III	II
污染等级 Contamination Class	3	2	2
额定电压 Rated Voltage [V]	160	160	320
额定电流 Rated Current [A]	8	8	8
额定冲击电压 Impulse withstand voltage [KV]	2.5	2.5	2.5
导线截面积[硬/柔] Conductor cross section [mm²]	0.2~1.5		


材料 Material

绝缘材料 Insulation Material	PA66
阻燃等级 Flame relardant rating	UL94V-0
导体材料 Conductor Material	Copper alloy
导体表面镀层 Plating of conductor surface	Sn plated


一般参数 Other Data

间距/极数 Pitch/Poles [mm]/[P]	3.5 , 3.81/2~24
剥线长度 Stripping Length [mm]	9~10
螺丝/扭矩 Screw/Torque(Max)[N.m]	/
工作温度 Operating temperature [°C]	-40~+105
焊锡温度 Soldering temperature	/
引针尺寸 Pin dimensions [mm]	/
PCB板孔径 PCB Hole Diameter [mm]	/

尺寸图



配件



WJ15EDGVHB-THT-3.5/3.81




WJ15EDGRHB-THT-3.5/3.81




WJ15EDGVC-THR-3.5/3.81



WJ15EDGRC-THR-3.5/3.81




WJ15EDGKR-3.81




WJ15EDGKNR-3.5



WJ15EDGLC-3.5/3.81



WJ15EDGVC-3.5/3.81



WJ15EDGRC-3.5/3.81



WJ15EDGVH3C-3.5



WJ15EDGRH3C-3.5



WJ15EDGRH3C-THT-3.5



WJ15EDGVH3C-THT-3.5