



Male Molded, Cables, Straight, Unshielded,  
Stainless Steel Screw



The catalog is for reference only. The actual specifications are subject to the product engineering drawings. version 1.0

### Connector Series: M12

Gender	Male
Coding	A,B,C,D
Locking Type	Fix Screw
Mounting Type	Straight
Part No	M12-X**-ST0-M02-SC*-XXX

### Technical Data

Standard	IEC61076-2-101
Ambient Temperatur	-25°C~+80°C
Insulation Resistance	≥100MΩ
Contact Resistance	≤5mΩ

# M12-X\*\*-ST0-M02-SC\*-XXX

M12 Circular Connector

Download Date:2026-07-07



IP Class	IP67
Mating Endurance	>100 Mating Cycles

## Material Data

Connector Carriers	PA
Connector Contacts	Copper Alloy With Gold Plated
Connector Nut/Screw	Stainless steel
Shielding	Unshielded
Connector Overmold	TPU

## Electrical Data & Mechanical Date

Contacts Pin [Pins]	3	4	5	6	8	12	17
Rated Current [A]	4	4	4/2	2	2	1.5	1.5
Voltage AC/DC [V]	250/250	250/250	60/60	30/30	30/30	30/30	30/30
Wire Range AWG/mm <sup>2</sup>	22/0.34	22/0.34	22,24/0.34,0.25	24/0.25	24/0.25	26/0.14	26/0.14
Cable Jacket	PUR/PVC						

## Dimensions

# M12-X\*\*-ST0-M02-SC\*-XXX

M12 Circular Connector

Download Date:2026-07-07

