

Rated current: 15A

Rated voltage: 300V

Use wire diameter: 28-12AWG

spacing:5.08mm

The catalog is for reference only. The actual specifications are subject to the product engineering drawings. version 1.0

UL/CUL

Use Group	B	C	D
Rate Voltage [V]	300	-	300
Rated Current [A]	15	-	10
Wire Range [AWG]	28-12		
Dielectric Voltage-Withstand	1.6KV		

IEC

Overvoltage Category	III	III	II
Contamination Class	3	2	2
Rated Voltage [V]	250	320	630
Rated Current [A]	24	24	24

TEL: +86-574-63510583 / 63510582 E-mail: cjw@china-wj.com
CIXI WANJIE ELECTRONIC CO.,LTD.
www.xn--chq953c.xn--fiqs8s

Impulse withstand voltage [KV]	4	4	4
Conductor cross section [mm²]	0.2-2.5		

Material


Insulation Material	PA66
Flame relardant rating	UL94V-0
Conductor Material	Copper alloy
Plating of conductor surface	Sn plated


Other Date

Pitch/Poles [mm]/[P]	5.08/1-30
Stripping Length [mm]	5-6
Screw/Torque(Max)[N.m]	-
Operating temperature [℃]	-40～+105
Soldering method	Wave soldering
Pin dimensions [mm]	0.75*0.7
PCB Hole Diameter [mm]	Ø1.3

Dimensions

PCB hole diagram


14.10
0.70
5.00
5.00
4.00
5.08XX+2.20
12.80
0.75
5.08
3.78
5.08(XX-1)


5.08(XX-1)
5.08
3.78
5.00
5.00
ø1.30
P.C.B. LAYOUT