



Rated current: 16A
 Rated voltage: 250V
 Use wire diameter: 22-14AWG
 spacing:7.5mm
 Install:



The catalog is for reference only. The actual specifications are subject to the product engineering drawings. version 1.0

-UL/CUL

Use Group	B	C	D
Rate Voltage [V]	250	-	250
Rated Current [A]	16	-	10
Wire Range [AWG]	22 ~ 14		
Dielectric Voltage-Withstand	1.5KV		

-IEC

Overvoltage Category	III	III	II
Contamination Class	3	2	2
Rated Voltage [V]	250	400	630
Rated Current [A]	24	24	24

Impulse withstand voltage [KV]	6	6	6
Conductor cross section [mm ²]	0.5~2.5		

Material

Insulation Material	PA66
Flame retardant rating	UL94V-0
Conductor Material	Copper alloy
Plating of conductor surface	Sn plated

Other Date

Pitch/Poles [mm]/[P]	7.5/2 ~ 24
Stripping Length [mm]	5 ~ 6
Screw/Torque(Max)[N.m]	M3/0.5
Operating temperature [°C]	-40 ~ +105
Soldering method	Wave soldering
Pin dimensions [mm]	Ø1.0
PCB Hole Diameter [mm]	Ø1.2

Dimensions

PCB hole diagram

WJ370-7.5

PCB SCREW TERMINAL BLOCK

Download Date:2026-07-08

