


Rated current: 15A

Rated voltage: 300V

Use wire diameter: 30-14AWG

spacing:3.5mm

Install: Wave soldering

The catalog is for reference only. The actual specifications are subject to the product engineering drawings. version 1.0

UL/CUL

Use Group	B	C	D
Rate Voltage [V]	300	-	300
Rated Current [A]	15	-	10
Wire Range [AWG]	30～14		
Dielectric Voltage-Withstand	1.6KV		

IEC

Overvoltage Category	III	III	II
Contamination Class	3	2	2
Rated Voltage [V]	200	250	500
Rated Current [A]	16	16	16

Impulse withstand voltage [KV]	2.5	2.5	2.5
Conductor cross section [mm²]	0.2~1.5		

Material


Insulation Material	PA66
Flame relardant rating	UL94V-0
Conductor Material	Copper alloy
Plating of conductor surface	Sn plated


Other Date

Pitch/Poles [mm]/[P]	3.5/2-24
Stripping Length [mm]	5-6
Screw/Torque(Max)[N.m]	M2/0.2
Operating temperature [℃]	-40 ~ +105
Soldering method	Wave soldering
Pin dimensions [mm]	0.5*0.8
PCB Hole Diameter [mm]	Ø1.2

Dimensions

PCB hole diagram


7.40
3.50XX+0.50
3.50
10.20
0.50
3.50
0.80
3.80
3.50(XX-1)
2.00


3.50(XX-1)
2.00
3.50
3.80
ø1.20
P.C.B. LAYOUT