

额定电流: 60A
额定电压: 600V
使用线径: 20-6AWG



目录仅供参考，实际规格依产品工程图为准 版本1.0

技术数据-UL (1059)

等级 Use Group	B	C	D
额定电压 Rate Voltage [V]	600	600	600
额定电流 Rated Current [A]	60	60	5
接线范围 Wire Range [AWG]	20 ~ 6		

技术参数-IEC (60947-7-1)

额定电压 Rated Voltage [V]	1000
额定电流 Rated Current [A]	57
单芯 Solid [mm²]	0.5-16.0
柔性导线 Flexible [mm²]	0.5-10.0
柔性导线带冷压头 Flexible with ferrule [mm²]	0.5-10.0
过电压类别 Overvoltage Category	III

污染等级 Contamination Class	3
额定冲击电压 Impulse withstand voltage [KV]	8


材料 Material

绝缘材料 Insulation Material	PA66
阻燃等级 Flame relardant rating	UL94V-0
导体材料 Conductor Material	Copper alloy
导体表面镀层 Plating of conductor surface	Sn plated

一般参数 Other Date

长/高/厚 Length/Height/Thickness [mm]	89.2/49.7/10.2
剥线长度 Stripping Length [mm]	18

尺寸图




适配产品



FUVA10-XX




DUV10-103




MUV10-10



PUV10-48




EB-35




EW-35



DGL2-35x7.5A



DGL2-35x7.5B



DGL2-35x7.5C



DGL2-35x7.5D