



额定电流: 20A

额定电压: 300V

使用线径: 28-12AWG



目录仅供参考，实际规格依产品工程图为准 版本1.0

技术数据-UL (1059)

| 等级 Use Group | B | C | D |
|------------------------|---------|-----|-----|
| 额定电压 Rate Voltage [V] | 300 | 300 | 600 |
| 额定电流 Rated Current [A] | 20 | 20 | 5 |
| 接线范围 Wire Range [AWG] | 28 ~ 12 | | |

技术参数-IEC

| | |
|----------------------------------|---------|
| 额定电压 Rated Voltage [V] | 630 |
| 额定电流 Rated Current [A] | 24 |
| 单芯 Solid [mm ²] | 0.2-4.0 |
| 柔性导线 Flexible [mm ²] | 0.2-4.0 |
| 过电压类别 Overvoltage Category | III |
| 污染等级 Contamination Class | 3 |

| | |
|---------------------------------------|---|
| 额定冲击电压 Impulse withstand voltage [KV] | 8 |
|---------------------------------------|---|

材料 Material

| | |
|-------------------------------------|--------------|
| 绝缘材料 Insulation Material | PA66 |
| 阻燃等级 Flame retardant rating | UL94V-0 |
| 导体材料 Conductor Material | Copper alloy |
| 导体表面镀层 Plating of conductor surface | Sn plated |

一般参数 Other Date

| | |
|----------------------------|------|
| 剥线长度 Stripping Length [mm] | 9-10 |
|----------------------------|------|

尺寸图

