


M12 母头成型式线缆，直头，非屏蔽

目录仅供参考，实际规格依产品工程图为准 版本1.0

## 连接器系列 Connector Series: M12

| | |
|---|---|
| 类型 Gender | Female 母 |
| 编码 Coding | A,B,C,D |
| 装配方式 Locking Type | Fix Screw 锁螺丝 |
| 安装类型 Mounting Type | Straight 直头 |
| 产品编码 Part No | M12-X**-ST0-F02-BC*-XXX |

## 技术参数 Technical Data

| | |
|---|---|
| 标准 Standard | IEC61076-2-101 |
| 工作温度 Ambient Temperatur | -25℃~+80℃ |
| 绝缘电阻 Insulation Resistance | ≥100MΩ |
| 接触电阻 Contact Resistance | ≤5mΩ |
| 防护等级 IP Class | IP67 |

| | |
|---|---|
| 机械寿命 Mating Endurance | >100 Mating Cycles |


## 材质说明 Material Data

| | |
|---|---|
| 胶芯材料 Connector Carriers | PA |
| 接触端子 Connector Contacts | Copper Alloy With Gold Plated 铜镀金 |
| 螺母/螺丝 Connector Nut/Screw | Copper Alloy With Nickel Plated 铜镀镍 |
| 屏蔽 Shielding | Unshielding 非屏蔽 |
| 连接器外模 Connector Overmold | TPU |

## 电气参数&机械参数 Electrical Data & Mechanical Date

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| Pin数 Contacts Pin [Pins] | 3 | 4 | 5 | 6 | 8 | 12 | 17 |
| 额定电流 Rated Current [A] | 4 | 4 | 4/2 | 2 | 2 | 1.5 | 1.5 |
| 电压 Voltage AC/DC [V] | 250/250 | 250/250 | 60/60 | 30/30 | 30/30 | 30/30 | 30/30 |
| 接线范围 Wire Range AWG/mm² | 22/0.34 | 22/0.34 | 22,24/0.34,0.25 (C-code) | 24/0.25 | 24/0.25 | 26/0.14 | 26/0.14 |
| 线缆外被 Cable Jacket | PUR/PVC | | | | | | |

## 尺寸图


M12X1.0
40.5 REF
L (mm)
ø14.5
WAN JIE
Cable Jacket PVC or PUR
线缆外被 PVC 或 PUR