

M12 母头成型式线缆, S-T-K-L-M Coding直头



目录仅供参考, 实际规格依产品工程图为准 版本1.0

连接器系列 Connector Series: M12

类型 Gender	Female 母
编码 Coding	S,T,K,L,M
装配方式 Locking Type	Fix Screw 锁螺丝
安装类型 Mounting Type	Straight 直头
产品编码 Part No	M12-X**-ST0-F02-BC*-XXX

技术参数 Technical Data

标准 Standard	IEC61076-2-111
工作温度 Ambient Temperatur	-25°C~+80°C
绝缘电阻 Insulation Resistance	≥100MΩ
接触电阻 Contact Resistance	≤5mΩ
防护等级 IP Class	IP67

机械寿命 Mating Endurance

&gt; 100 Mating Cycles

## 材质说明 Material Data

胶芯材料 Connector Carriers	PA
接触端子 Connector Contacts	Copper Alloy With Gold Plated 铜镀金
螺母/螺丝 Connector Nut/Screw	Copper Alloy With Nickel Plated 铜镀镍
密封胶圈 Seal/O-Ring	FKM 氟橡胶
屏蔽 Shielding	Unshielded/Shielded 非屏蔽/屏蔽
连接器外模 Connector Overmold	TPU

## 电气参数&amp;机械参数 Electrical Data &amp; Mechanical Date

Available Coding 防插错编码	S-Coding T-Coding K-Coding L-Coding M-Coding				
额定电流 Rated Current [A]	16(03Pin), 12(04Pin )	12	12	16	8
额定电压 Rated Voltage [V]	630	63	630	63	630
接线范围 Wire Range AWG/mm <sup>2</sup>	16/1.5	16/1.5	16/1.5	16/1.5	18/1.0
线缆外被 Cable Jacket	PUR/PVC				

## 尺寸图

