



额定电流: 12A

额定电压: 300V

使用线径: 24-16AWG

间距:5.08mm



目录仅供参考，实际规格依产品工程图为准 版本1.0

技术数据-UL/CUL

| 等级 Use Group | B | C | D |
|----------------------------------|-------|---|-----|
| 额定电压 Rate Voltage [V] | 300 | - | 300 |
| 额定电流 Rated Current [A] | 12 | - | 10 |
| 接线范围 Wire Range [AWG] | 24-16 | | |
| 耐电压 Dielectric Voltage-Withstand | 1.6KV | | |

技术参数-IEC

| 过电压类别 Overvoltage Category | III | III | II |
|---------------------------------------|-----|-----|-----|
| 污染等级 Contamination Class | 3 | 2 | 2 |
| 额定电压 Rated Voltage [V] | 320 | 320 | 630 |
| 额定电流 Rated Current [A] | 12 | 12 | 12 |
| 额定冲击电压 Impulse withstand voltage [KV] | 4 | 4 | 4 |

导线截面积[硬/柔] Conductor cross section [mm²]

0.2-1.5/0.2-2.5


材料 Material

| | |
|-------------------------------------|--------------|
| 绝缘材料 Insulation Material | PA66 |
| 阻燃等级 Flame retardant rating | UL94V-0 |
| 导体材料 Conductor Material | Copper alloy |
| 导体表面镀层 Plating of conductor surface | Sn plated |

一般参数 Other Date

| | |
|---------------------------------|------------|
| 间距/极数 Pitch/Poles [mm]/[P] | 5.08/2-24 |
| 剥线长度 Stripping Length [mm] | 11-12 |
| 螺丝/扭矩 Screw/Torque(Max)[N.m] | - |
| 工作温度 Operating temperature [°C] | -40 ~ +105 |

尺寸图



适配产品



WJ2EDGV-5.08



WJ2EDGR-5.08



WJ2EDGVC-5.08



WJ2EDGRC-5.08




WJ2EDGRHB-THR-5.08



WJ2EDGVHB-THR-5.08

配套部件



WJ2EDG-PWI