




Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权,否则禁止转让、复制、利用、交还文件内容,侵犯者将负法律责任。未经许可擅自复制或交还文件,侵权必究。



General Tolerances										
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 10	over 10 to 100	over 100 to 100	over 100 to 100
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

4	Pin	Copper Alloy	M2.5/Sn Plated
3	Screw	Steel	M2.5/Zn Plated
2	Spring	Stainless Steel	
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

DES.	CY	DATE	23.11.28	UNITS	mm	THIRD ANGLE PROJECTION		
CHK.	YangHJ	DATE	23.11.28	SIZE	A4	TYPE: CUSTOMER DRAWING		SHEET 1 of 1
APP.	JASON	DATE	23.11.28	SCALE	3:1	DRAWING TYPE: SP-03		REV V0
慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						PART NO.: WJ301-5.0-XXP-1Y-00A		

REVISION RECORD					
REV.	ESCRPTION		ECN No.	APPROVED	DATE
V0	新发行			CY	23.11.28
UL/CUL 技术 参数			UL1059		
UL/CUL Technical Data					
等 级	Use Group		B	C	D
额定电压	Rated Voltage	[V]	300	-	300
额定电流	Rated Current	[A]	16	-	10
接线范围	Wire Range		22-14		
单/多芯线	Solid/Stranded	[AWG]			
耐电压	Withstanding Voltage		1600V/1Min		
IEC 技术参数					
IEC Technical Data					
过电压类别	Overvoltage Category		III	III	II
污染等级	Contamination Class		3	2	2
额定电压	Rated Voltage	[V]	250	400	630
额定电流	Rated Current	[A]	17.5	17.5	17.5
额定冲击电压	Impulse withstand voltage		4.0	4.0	4.0
	[KV]				
导线截面积	Conductor cross section		0.5-1.5		
硬质/柔性导线	Solid/ flexible		[mm²]		
一般参数 Other Data					
间距 Pitch /极数 Poles	[mm]/ [P]		5.0/02~24		
剥线长度 Stripping Length	[mm]		5~6		
螺丝 Screw/扭矩 Torque(Max)	[N.m]		M2.5/0.4		
工作温度 Operating temperature	[°C]		-40~105		
焊锡温度 Soldering temperature			260°C/5S		