





Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除特授予明确授权，否则禁止转让、复制、利用、交还本文件的内容。侵犯者将承担法律责任。未经许可擅自复制或传播，侵权者将承担法律责任。



P.C.B. LAYOUT



General Tolerances

General Tolerances								—	∇	⊥
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

REVISION RECORD

REV.	DESCRIPTION	ECN No.	APPROVED	DATE
V0	新发行		CY	23.11.21

UL/CUL 技术参数

UL/CUL Technical Data



等级	Use Group	B	C	D
额定电压	Rated Voltage [V]	300	-	300
额定电流	Rated Current [A]	12	-	10
接线范围	Wire Range	26-14		
单/多芯线	Solid/Stranded [AWG]			
耐电压	Withstanding Voltage	1600V/1Min		

IEC 技术参数

IEC Technical Data



过电压类别	Overvoltage Category	III	III	II
污染等级	Contamination Class	3	2	2
额定电压	Rated Voltage [V]	250	400	630
额定电流	Rated Current [A]	17.5	17.5	17.5
额定冲击电压	Impulse withstand voltage [KV]	4.0	4.0	4.0

导线截面积	Conductor cross section	0.5-1.5		
硬质/柔性导线	Solid/flexible [mm ²]			

一般参数 Other Data

间距	Pitch /极数 Poles [mm]/[P]	5.0 / 02-24
剥线长度	Stripping Length [mm]	5-6
螺丝	Screw/扭矩 Torque(Max) [N.m]	M2.5/0.4
工作温度	Operating temperature [°C]	-40~105
焊锡温度	Soldering temperature	260°C/5S

ITEM	NAME OF PART	MATERIAL	NOTES
4	Header pin	Copper Alloy	Sn Plated
3	Screw	Steel	M2.5/Zn Plated
2	Cage	Copper Alloy	M2.5/Ni Plated
1	Housing	PA66	UL94V-0
DES.	CY	DATE 23.11.21	UNITS mm
CHK.	YangHJ	DATE 23.11.21	SIZE A4
APP.	JASON	DATE 23.11.21	SCALE 4:1
THIRD ANGLE PROJECTION		TYPE: CUSTOMER DRAWING	
DRAWING TYPE: SP-03		SHEET 1 of 1	
REV		V0	
PART NO.: WJ127-5.0-XXP-1Y-00A			



慈溪市万捷电子有限公司
CIXI WANJIE ELECTRONIC CO., LTD

PART NO.:
WJ127-5.0-XXP-1Y-00A