





## REVISION RECORD

REV.	DESCRIPTION	ECN No.	APPROVED	DATE
0	新发行		YaoFei	24.01.25



P.C.B. LAYOUT



Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权，否则禁止转让、复制、利用、交流本文档的内容。侵犯者将负责赔偿责任。本公司保留对涉及发明、实用新型和外观专利的所有权利。

General Tolerances										—		
variable range	to	over 6	over 10	over 30	over 60	over 100	over 160	over 100	over 160	over 100	over 100	over 100
		to 6	to 10	to 30	to 60	to 100	to 160	to 10	to 100	to 100	to 100	to 100
tolerance		±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60	

UL/CUL 技术参数  
UL/CUL Technical Data



等级	Use Group	B	C	D
额定电压	Rated Voltage [V]	300	-	300
额定电流	Rated Current [A]	15	-	10
接线范围	Wire Range		-	
单/多芯线	Solid/Stranded [AWG]			
耐电压	Withstanding Voltage	1600V/1Min		

IEC 技术参数  
IEC Technical Data



过电压类别	Overvoltage Category	III	III	II
污染等级	Contamination Class	3	2	2
额定电压	Rated Voltage [V]	320	320	630
额定电流	Rated Current [A]	12	12	12
额定冲击电压	Impulse withstand voltage [KV]	4.0	4.0	4.0
导线截面积	Conductor cross section			
硬质/柔性导线	Solid/ flexible [mm <sup>2</sup> ]			

## 一般参数 Other Data

间距 Pitch /极数 Poles [mm] / [P]	5.08 / 02-24
工作温度 Operating temperature [°C]	-40~105
焊锡温度 Soldering temperature	260°C/5S
引针尺寸 Pin Dimensions [mm]	0.4*1.1
PCB板孔径 PCB Hole Diameter [mm]	Ø1.4
符合RoHS环保要求	

符合RoHS环保要求

4	Nut	Copper Alloy	M2.5
3	Clamp	Copper Alloy	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

DES.	YaoFei	DATE	24.01.25	UNITS	mm	THIRD ANGLE PROJECTION	REV.
CHK.	YangHJ	DATE	24.01.25	SIZE	A4	TYPE: CUSTOMER DRAWING	SHEET 1 of 1
APP.	JASON	DATE	24.01.25	SCALE	2:1	DRAWING TYPE: SP-03	REV. 0
WANJIE 慈溪市万捷电子有限公司						PART NO.: WJ2EDGAM-5.08-XXP-1Y-00A	

