



General Tolerances											
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 210	over 210 to 260	over 260 to 310	over 310 to 360	over 360 to 410
tolerance	± 0.20	± 0.30	± 0.50	± 0.70	± 1.00	± 1.30	± 1.60	0.10	0.30	0.60	

ITEM	NAME OF PART	MATERIAL	NOTES	WANJIE 慈溪市万捷电子有限公司		PART NO.: WJ2EDGKDGB-5.08-XXP-1Y-00A	
6	Hook	Pom	UL94V-HB	DES.	YaoFei	DATE	23.12.25
5	Button	Pom	UL94V-HB	CHK.	YangHJ	DATE	23.12.25
4	Clamp	Copper Alloy	Sn Plated	APP.	JASON	DATE	23.12.25
3	Spring	Stainless Steel	/	ITEM	NAME OF PART	MATERIAL	NOTES
2	Cover	PA66	UL94V-0	WANJIE		PART NO.: WJ2EDGKDGB-5.08-XXP-1Y-00A	
1	Housing	PA66	UL94V-0				

UL/CUL 技术参数		UL/CUL Technical Data		cULus	
等级	Use Group	B	C	D	
额定电压	Rated Voltage [V]	300	-	300	
额定电流	Rated Current [A]	20	-	10	
接线范围	Wire Range				
单/多芯线	Solid/Stranded [AWG]				28-12
耐电压	Withstanding Voltage				1600V/1Min
IEC 技术参数					
IEC Technical Data					
过电压类别	Overvoltage Category	III	III	II	
污染等级	Contamination Class	3	2	2	
额定电压	Rated Voltage [V]	250	320	630	
额定电流	Rated Current [A]	12	12	12	
额定冲击电压	Impulse withstand voltage [KV]	4.0	4.0	4.0	
导线截面积	Conductor cross section				0.2-2.5
硬质/柔性导线	Solid/ flexible [mm ²]				
一般参数					
间距	Pitch /极数 Poles [mm] / [P]				5.08 / 2~24
剥线长度	Stripping Length [mm]				7~8
工作温度	Operating temperature [°C]				-40~105
符合RoHS环保要求					