





Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非经予明确授权，否则禁止转让、复制、利用、交流本文件的内容。侵犯者将承担赔偿责任，侵权者将承担赔偿责任。



General Tolerances								— ▯ ⊥		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

2	Pin	Copper Alloy	Sn Plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES



DES.	YaoFei	DATE	24.01.22	UNITS	mm	THIRD ANGLE PROJECTION	
CHK.	YangHJ	DATE	24.01.22	SIZE	A4	TYPE: CUSTOMER DRAWING	
APP.	JASON	DATE	24.01.22	SCALE	5:2	DRAWING TYPE: SP-03	
慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						PART NO.: WJ2EDGVC-7.62-XXP-1Y-00A	
						REV	0

REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
0	新发行		YaoFei	24.01.22
UL/CUL 技术参数 UL/CUL Technical Data 等级 Use Group B C D 额定电压 Rated Voltage [V] 300 - 300 额定电流 Rated Current [A] 15 - 10 接线范围 Wire Range 单/多芯线 Solid/Stranded [AWG] - 耐压 Withstanding Voltage 1600V/1Min IEC 技术参数 IEC Technical Data 过电压类别 Overvoltage Category III III II 污染等级 Contamination Class 3 2 2 额定电压 Rated Voltage [V] 400 630 630 额定电流 Rated Current [A] 15 15 15 额定冲击电压 Impulse withstand voltage [KV] 6.0 6.0 6.0 导线截面积 Conductor cross section 硬质/柔性导线 Solid/ flexible [mm²] - 一般参数 Other Data 间距 Pitch /极数 Poles [mm]/[P] 7.62 / 02~24 工作温度 Operating temperature [°C] -40~105 焊锡温度 Soldering temperature 260°C/5S 引脚尺寸 Pin Dimensions [mm] 1.0*1.0 PCB板孔径 PCB Hole Diameter [mm] Ø1.7 符合RoHS环保要求				