




Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非经予明确授权，否则禁止转让、复制、利用、交流本文件的内容。侵犯者将承担赔偿责任，实用新型和外观设计专利的所有权利。



General Tolerances								— □ ⊥		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60



2	Pin	Copper Alloy	Sn Plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

5			6				
REVISION RECORD							
REV.	DESCRIPTION			ECN No.	APPROVED	DATE	
V0	新发行				WangP	23.12.13	
		UL/CUL 技术参数					
		UL/CUL Technical Data					
		等级	Use Group	B	C	D	
		额定电压	Rated Voltage [V]	600	-	600	
		额定电流	Rated Current [A]	15	-	5	
		接线范围	Wire Range	-			
		单/多芯线	Solid/Stranded [AWG]				
		耐电压	Withstanding Voltage	2200V/1Min			
		IEC 技术参数		IEC61984			
		IEC Technical Data					
		过电压类别	Overvoltage Category	III	III	II	
		污染等级	Contamination Class	3	2	2	
		额定电压	Rated Voltage [V]	630	1000	1000	
		额定电流	Rated Current [A]	15	15	15	
		额定冲击电压	Impulse withstand voltage [KV]	6.0	6.0	6.0	
		导线截面积	Conductor cross section	-			
		硬质/柔性导线	Solid/ flexible [mm²]				
		一般参数		Other Data			
		间距	Pitch /极数	Poles [mm] / [P]	10.16 / 02~12		
剥线长度	Stripping Length [mm]	-					
螺丝	Screw/扭矩	Torque(Max) [N.m]	-				
工作温度	Operating temperature [°C]	-40~105					
符合RoHS环保要求							

WangP	DATE	23.12.13	UNITS	mm	THIRD ANGLE PROJECTION	
YangHJ	DATE	23.12.13	SIZE	A4	TYPE: CUSTOMER DRAWING	SHEET 1 of 1
JASON	DATE	23.12.13	SCALE	3:1	DRAWING TYPE: SP-03	REV V0



慈溪市万捷电子有限公司
CIXI WANJIE ELECTRONIC CO., LTD

PART NO.:
WJ2EDGR-10.16-XXP-2Y-00A