



Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权, 否则禁止转让、复制、利用、交流本文件的内容。侵犯者将负赔偿责任。本公司保留对涉及发明、实用新型和外观设计的所有权利。



General Tolerances								—		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

5	Spring	Stainless Steel	
4	Clamp	Copper Alloy	Sn Plated
3	Button	POM	UL94-HB
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

REVISION RECORD									
REV.	DESCRIPTION				ECN No.	APPROVED	DATE		
V0	新发行					WangP	23.10.16		
					UL/CUL 技术参数 UL/CUL Technical Data 				
等 级					Use Group	B	C	D	
额定电压					Rated Voltage [V]	300	-	300	
额定电流					Rated Current [A]	12	-	10	
接线范围					Wire Range	24-16			
单/多芯线					Solid/Stranded [AWG]				
耐电压					Withstanding Voltage	1600V/1Min			
IEC 技术参数					IEC 61984				
IEC Technical Data									
过电压类别					Overvoltage Category	III	III	II	
污染等级					Contamination Class	3	2	2	
额定电压					Rated Voltage [V]	320	320	630	
额定电流					Rated Current [A]	12	12	12	
额定冲击电压					Impulse withstand voltage [KV]	4	4	4	
导线截面积					Conductor cross section	0.2-1.5/0.2-2.5			
硬质/柔性导线					Solid/ flexible [mm²]				
一般参数					Other Data				
间距					Pitch [mm]	5.0			
极数					Poles [P]	02~24			
剥线长度					Stripping Length [mm]	11~12			
螺丝					Screw	-			
扭矩					Torque(Max) [N.m]	-			
工作温度					Operating temperature [°C]	-40~105			
符合RoHS环保要求									