



General Tolerances										—	□	上	
variable range	to	over 6	over 10	over 30	over 60	over 100	over 160	to	over 10	over 100	to		
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60			
	6	10	30	60	100	160	10	100	100	100			

1

2

3

4

5

FOR-0371 Rev.1.0

REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
V0	新发行		YuCZ	23.12.06

UL/CUL 技术参数 UL/CUL Technical Data							
等级	Use Group	B	C	D			
额定电压	Rated Voltage [V]	300	300	300			
额定电流	Rated Current [A]	55	55	10			
接线范围	Wire Range	-					
单/多芯线	Solid/Stranded [AWG]	-					
耐电压	Withstanding Voltage	1600V/1Min					
IEC 技术参数 IEC Technical Data							
IEC61984							
过电压类别	Overvoltage Category	III	III	II			
污染等级	Contamination Class	3	2	2			
额定电压	Rated Voltage [V]	1000	1000	1000			
额定电流	Rated Current [A]	76	76	76			
额定冲击电压	Impulse withstand voltage [KV]	8.0	8.0	6.0			
导线截面积	Conductor cross section	-					
硬质/柔性导线	Solid/ flexible [mm <sup>2</sup> ]	-					
一般参数 Other Data							
间距	Pitch / 极数 Poles [mm] / [P]	10.16 / 02~18					
工作温度	Operating temperature [°C]	-40~105					
焊锡温度	Soldering temperature	260°C/5S					
符合RoHS环保要求							
2	Pin	Copper Alloy		Sn Plated			
1	Housing	PA66		UL94V-0			
ITEM NAME OF PART MATERIAL NOTES							
DES.	YuCZ	DATE	23.12.06	UNITS mm THIRD ANGLE PROJECTION			
CHK.	YangHJ	DATE	23.12.06	SIZE A4 TYPE: CUSTOMER DRAWING SHEET 1 of 1			
APP.	JASON	DATE	23.12.06	SCALE 7:5 DRAWING TYPE: SP-03 REV V0			
 慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD							
PART NO.: WJ3EDGRRC-10.16-XXP-1Y-00A							

A

B

C

D