




Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权，否则禁止转让、复制、利用、交流本文件的内容。侵犯者将承担法律责任。本公司保留对涉及发明、实用新型和外观设计的所有权利。

1	2	3	4	5	6
---	---	---	---	---	---

REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
V0	新发行		YuCZ	23.11.29



General Tolerances										—	▤	⊥
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 10	over 10 to 100	over 100 to 100			
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60		

UL/CUL 技术参数		UL/CUL Technical Data					
等级	Use Group	B	C	D			
额定电压	Rated Voltage [V]	300	-	300			
额定电流	Rated Current [A]	15	-	10			
接线范围	Wire Range	28-12					
单/多芯线	Solid/Stranded [AWG]						
耐电压	Withstanding Voltage	1600V/1Min					
IEC 技术参数		IEC61984					
IEC Technical Data							
过电压类别	Overvoltage Category	III	III	II			
污染等级	Contamination Class	3	2	2			
额定电压	Rated Voltage [V]	400	630	1000			
额定电流	Rated Current [A]	12	12	12			
额定冲击电压	Impulse withstand voltage [KV]	6.0	6.0	6.0			
导线截面积	Conductor cross section	0.2-2.5					
硬质/柔性导线	Solid/ flexible [mm²]						
一般参数 Other Data							
间距 Pitch / 极数 Poles [mm] / [P]				7.62 / 02-24			
剥线长度 Stripping Length [mm]				7-8			
螺丝 Screw/ 扭矩 Torque(Max) [N.m]				M3/0.5			
工作温度 Operating temperature [°C]				-40~105			
符合RoHS环保要求							
6	NUT	Copper Alloy		M2.5			
5	Screw	Steel		M3/Zn Plated			
4	Cage	Copper Alloy		M3/Ni Plated			
3	Pin	Copper Alloy		Sn Plated			
2	Cover	PA66		UL94V-0			
1	Housing	PA66		UL94V-0			
ITEM	NAME OF PART	MATERIAL		NOTES			

DES.	YuCZ	DATE	23.11.29	UNITS	mm	THIRD ANGLE PROJECTION		⊕
CHK.	YangHJ	DATE	23.11.29	SIZE	A4	TYPE: CUSTOMER DRAWING		SHEET 1 of 1
APP.	JASON	DATE	23.11.29	SCALE	2:1	DRAWING TYPE: SP-03		REV V0
慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						PART NO.: WJ2EDGKRN-7.62-XXP-1Y-00A		

1	2	3	4	5	6
---	---	---	---	---	---