




Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除获给予明确授权, 否则禁止转让、复制、利用、交流本文件的内容。侵犯者将承担赔偿责任。使用新型和外观专利的所有权利。




08~24P尺寸图




08~24P尺寸图



02~03P尺寸图



04~07P尺寸图



53.40(REF)

REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
0	新发行		YaoFei	23.12.22

UL/CUL 技术参数				
UL/CUL Technical Data				
等级	Use Group	B	C	D
额定电压	Rated Voltage [V]	300	-	300
额定电流	Rated Current [A]	15	-	10
接线范围	Wire Range	28-12		
单/多芯线	Solid/Stranded [AWG]			
耐压	Withstanding Voltage	1600V/1Min		
IEC 技术参数				
IEC Technical Data				
过电压类别	Overvoltage Category	III	III	II
污染等级	Contamination Class	3	2	2
额定电压	Rated Voltage [V]	250	320	630
额定电流	Rated Current [A]	12	12	12
额定冲击电压	Impulse withstand voltage [KV]	4.0	4.0	4.0
导线截面积	Conductor cross section	0.2-2.5		
硬质/柔性导线	Solid/ flexible [mm²]			
一般参数 Other Data				
间距 Pitch / 极数 Poles	[mm] / [P]	5.08 / 02~24		
剥线长度	Stripping Length [mm]	7~8		
螺丝 Screw/ 扭矩 Torque(Max)	[N.m]	M3/0.5		
工作温度	Operating temperature [°C]	-40~105		
7	Screw 2	Steel	M2.5/Zn Plated	
6	Housing 2	PA66	UL94V-0	
5	Screw 1	Steel	M3/Zn Plated	
4	Cage	Copper Alloy	M3/Ni Plated	
3	Pin	Copper Alloy	Ni Plated	
2	Cover	PA66	UL94V-0	
1	Housing 1	PA66	UL94V-0	
ITEM	NAME OF PART	MATERIAL	NOTES	

General Tolerances								—	∇	⊥
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

DES.	YaoFei	DATE	23.12.22	UNITS	mm	THIRD ANGLE PROJECTION			
CHK.	YangHJ	DATE	23.12.22	SIZE	A4	TYPE: CUSTOMER DRAWING		SHEET 1 of 1	
APP.	JASON	DATE	23.12.22	SCALE	1:1	DRAWING TYPE: SP-03		REV	0
 慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						PART NO.: WJ2EDGKRZM-5.08-XXP-1Y-00A			