




Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权, 否则禁止转让、复制、利用、交流本文件的内容。侵犯者将负赔偿责任。本公司保留对涉及发明、实用新型和外观设计专利的所有权利。



REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
V0	新发行		YaoFei	24.09.27

UL/CUL	技术 参数	UL1059		
UL/CUL	Technical Data			
等 级	Use Group	B	C	D
额定电压	Rated Voltage [V]	600	600	-
额定电流	Rated Current [A]	35	35	-
接线范围 单/多芯线	Wire Range Solid/Stranded [AWG]	24-8		
耐电压	Withstanding Voltage	2200V/1Min		
IEC 技术参数	IEC61984			
IEC Technical Data				
过电压类别	Overvoltage Category	III	III	II
污染等级	Contamination Class	3	2	2
额定电压	Rated Voltage [V]	1000	1000	1000
额定电流	Rated Current [A]	41	41	41
额定冲击电压 Impulse withstand voltage	[KV]	8.0	8.0	6.0
导线截面积 硬质/柔性导线	Conductor cross section Solid/ flexible [mm ²]	0.2-6.0		
一般参数	Other Data			
间距 Pitch / 极数 Poles	[mm] / [P]	7.62 / 02~12		
剥线长度 Stripping Length	[mm]	14~15		
工作温度 Operating temperature	[°C]	-40~105		
符合RoHS环保要求				

General Tolerances								—		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

6	Screw	Steel	M3/Zn Plated
5	Spring	Stainless steel	
4	Clamp	Copper Alloy	Sn Plated
3	Side Housing 2	PA66	UL94V-0
2	Side Housing 1	PA66	UL94V-0
1	Mid Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

DES.	YaoFei	DATE	24.09.27	UNITS	mm	THIRD ANGLE PROJECTION		
CHK.	YangHJ	DATE	24.09.27	SIZE	A4	TYPE: CUSTOMER DRAWING	SHEET 1 of 1	
APP.	JASON	DATE	24.09.27	SCALE	2:1	DRAWING TYPE: SP-03	REV	VO
 慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						PART NO.: WJ3EDGKVM-7.62-XXP-1Y-00A		