





Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除经授予明确授权，否则禁止转让、复制、利用、交流本文件的内容。侵犯者将承担赔偿责任。本公司保留对专利及发明、实用新型和外观设计的所有权利。



REVISION RECORD				
REV.	ESCRPTION	ECN No.	APPROVED	DATE
V0	新发行		WuBW	24.06.14

UL/CUL 技术参数 UL/CUL Technical Data		cULus		
等级	Use Group	B	C	D
额定电压	Rated Voltage [V]	150	-	-
额定电流	Rated Current [A]	5	-	-
接线范围	Wire Range	26-18		
单/多芯线	Solid/Stranded [AWG]			
耐电压	Withstanding Voltage	1300V/1Min		
IEC 技术参数 IEC Technical Data		IEC60947-7-4		
过电压类别	Overvoltage Category	III	III	II
污染等级	Contamination Class	3	2	2
额定电压	Rated Voltage [V]	63	160	320
额定电流	Rated Current [A]	6	6	6
额定冲击电压	Impulse withstand voltage [KV]	2.5	2.5	2.5
导线截面积	Wire cross section	0.2~0.5		
硬质/柔性导线	Solid/flexible [mm ²]			
材料 Material				
绝缘材料	Insulation Material	PA66		
阻燃等级	Flammability	UL94V-0		
导体材料	Conductor Material	铜合金 Copper alloy		
导体表面镀层	Conductor Plating	镀锡 Sn Plated		
一般参数 Other Data				
间距	Pitch / 极数 Poles [mm] / [P]	2.54/ 01~30		
剥线长度	Stripping Length [mm]	11		
螺丝	Screw/ 扭矩 Torque(Max) [N.m]	/		
工作温度	Operating temperature [°C]	-40~105		
焊接温度	Soldering temperature [°C]	260°C/5S		
引针尺寸	Pin Dimensions [mm]	0.7*0.4		
PCB板孔径	PCB Hole Diameter [mm]	Ø1.0		

General Tolerances

								—	∕	⊥
variable range	to	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

5	Spring	Stainless steel	/	DES.	WuBW	DATE	24.06.14	UNITS	mm	THIRD ANGLE PROJECTION			
4	Pin header	Copper Alloy	Sn Plated	CHK.	HuHT	DATE	24.06.14	SIZE	A4	TYPE: CUSTOMER DRAWING		SHEET 1 of 1	
3	Button	POM	UL94-HB	APP.	Jason	DATE	24.06.14	SCALE	3:1	DRAWING TYPE: SP-03		REV	V0
2	Cover	PA66	UL94V-0	 慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						PART NO.: WJ211R-2.54-XXP-1Y-00A			
1	Housing	PA66	UL94V-0										
ITEM	NAME OF PART	MATERIAL	NOTES										