





Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除经许可于明确授权外，未经许可擅自复制或传播本文件内容，侵犯者将承担法律责任。本公司保留对专利及发明、实用新型和外观设计的所有权利。



General Tolerances								—	∕	⊥
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60



ITEM	NAME OF PART	MATERIAL	NOTES
4	Spring	Stainless steel	/
3	Pin header	Copper Alloy	Sn Plated
2	Button	LCP	UL94V-0
1	Housing	LCP	UL94V-0

REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
V0	新发行		Wubw	24.06.27
UL/CUL 技术参数 UL/CUL Technical Data 等级 Use Group B C D 额定电压 Rated Voltage [V] 300 - 300 额定电流 Rated Current [A] 10 - 10 接线范围 Wire Range 单/多芯线 Solid/Stranded [AWG] 24~16 耐电压 Withstanding Voltage 1600V/1Min IEC 技术参数 IEC Technical Data IEC60947-7-4 过电压类别 Overvoltage Category III III II 污染等级 Contamination Class 3 2 2 额定电压 Rated Voltage [V] 250 320 500 额定电流 Rated Current [A] 17.5 17.5 17.5 额定冲击电压 Impulse withstand voltagea [KV] 4.0 4.0 4.0 导线截面积 Conductor cross section 硬质/柔性导线 Solid/flexible [mm²] 0.2-1.5 材料 Material 绝缘材料 Insulation Material LCP 阻燃等级 Imflammability UL94V-0 导体材料 Contactor Material 铜合金 Copper alloy 导体表面镀层 Contactive Coating 镀锡 Sn Plated 一般参数 Other Data 间距 Pitch /极数 Poles [mm] / [P] 5.0/2~24 工作温度 Operating temperatur [°C] -40~130 剥线长度 Stripping Length [mm] 7-8 焊锡温度 Soldering temperature 285°C/10S 引针尺寸 Pin Dimensions [mm] 0.8*0.4				
DES. Wubw DATE 24.06.27 UNITS mm THIRD ANGLE PROJECTION CHK. HuHT DATE 24.06.27 SIZE A4 TYPE: CUSTOMER DRAWING SHEET 1 of 1 APP. Jason DATE 24.06.27 SCALE 2:1 DRAWING TYPE: SP-03 REV V0 慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD PART NO.: WJ212RS-THR-5.0-XXP-1Y-00A				
FOR-0371 Rev.1.0				