




Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权,否则禁止转让、复制、利用、交流本文件的内容。侵犯者将承担赔偿责任。本公司保留对涉及发明、实用新型和小发明专利的所有权利。



REVISION RECORD				
REV.	ESCRPTION	ECN No.	APPROVED	DATE
V0			ZhaoXY	25.07.18

UL/CUL 技术参数		UL1059		
UL/CUL Technical Data				
等 级	Use Group	B	C	D
额定电压	Rated Voltage [V]	300	50	300
额定电流	Rated Current [A]	10	10	10
接线范围	Wire Range	28-16		
单/多芯线	Solid/Stranded [AWG]			
耐电压	Withstanding Voltage	1600V/1Min		
IEC 技术参数		IEC60947-7-4		
IEC Technical Data				
过电压类别	Overvoltage Category	III	III	II
污染等级	Contamination Class	3	2	2
额定电压	Rated Voltage [V]	320	320	630
额定电流	Rated Current [A]	10	10	10
额定冲击电压		4	4	4
Impulse withstand voltage	[KV]			
导线截面积	Conductor cross section	0.2~1.5		
硬质/柔性导线	Solid/ flexible [mm²]			
材 料 Material				
绝缘材料	Insulation Material	PA66		
阻燃等级	Imflammability	UL94V-0		
导体材料	Contactur Material	铜合金 Copper alloy		
导体表面镀层	Contactive Coating	镀锡 Sn Plated		
一般参数 Other Data				
间距 Pitch /极数 Poles	[mm] / [P]	5.0/ 02~12		
剥线长度	Stripping Length [mm]	10-12		
工作温度	Operating temperature [°C]	-40~105		
焊锡温度	Soldering temperature [°C]	260°C/5S		
引针尺寸	Pin Dimensions [mm]	0.4*0.8		
PCB板孔径	PCB Hole Diameter [mm]	Ø1.2		

General Tolerances								—	∇	⊥
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

6	Pin Header	Copper Alloy	Sn Plated
5	Spring	Stainless Steel	-
4	Button	PA66	UL94V-0
3	Cover	PA66	UL94V-0
2	Housing2	PA66	UL94V-0
1	Housing1	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

DES.	ZhaoXY	DATE	25.07.18	UNITS	mm	THIRD ANGLE PROJECTION	D
CHK.	HuHT	DATE	25.07.18	SIZE	A4	TYPE: CUSTOMER DRAWING	
APP.	Jason	DATE	25.07.18	SCALE	2:1	DRAWING TYPE: SP-03	
WANJI 慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						PART NO.: WJ253-5.0-XXP-1Y-00A	