





Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权, 否则禁止转让、复制、利用、交流本文件的内容。侵犯者将负赔偿责任。本公司保留对涉及发明、实用新型和外观设计专利的所有权利。



P.C.B. LAYOUT



General Tolerances

General Tolerances								—		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

5	Spring	Stainless steel	/
4	Pin header	Copper Alloy	Sn Plated
3	Button	POM	UL94-HB
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

DES.	WuBW	DATE	24.06.14	UNITS	mm	THIRD ANGLE PROJECTION		
CHK.	HuHT	DATE	24.06.14	SIZE	A4	TYPE: CUSTOMER DRAWING	SHEET 1 of 1	
APP.	Jason	DATE	24.06.14	SCALE	3:1	DRAWING TYPE: SP-03	REV	VO
 慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						PART NO.: WJ211V-2.54-XXP-1Y-00A		

REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
V0	新发行		WuBW	24.06.14

UL/CUL 技术参数				
UL/CUL Technical Data				
等级	Use Group	B	C	D
额定电压	Rated Voltage [V]	150	-	-
额定电流	Rated Current [A]	5	-	-
接线范围	Wire Range	26-18		
单/多芯线	Solid/Stranded [AWG]			
耐电压	Withstanding Voltage	1300V/1Min		
IEC 技术参数		IEC60947-7-4		
IEC Technical Data				
过电压类别	Overvoltage Category	III	III	II
污染等级	Contamination Class	3	2	2
额定电压	Rated Voltage [V]	63	160	320
额定电流	Rated Current [A]	6	6	6
额定冲击电压	Impulse withstand voltage [KV]	2.5	2.5	2.5
导线截面积	Wire cross section	0.2~0.5		
硬质/柔性导线	Solid/ flexible [mm ²]			
材 料		Material		
绝缘材料	Insulation Material	PA66		
阻燃等级	Flammability	UL94V-0		
导体材料	Conductor Material	铜合金 Copper alloy		
导体表面镀层	Conductor Plating	镀锡 Sn Plated		
一般参数		Other Data		
间距 Pitch / 极数 Poles	[mm] / [P]	2.54/ 01~30		
剥线长度	Stripping Length [mm]	11		
螺丝 Screw/ 扭矩 Torque(Max)	[N.m]	/		
工作温度	Operating temperature [°C]	-40~105		
焊锡温度	Soldering temperature [°C]	260°C/5S		
引针尺寸	Pin Dimensions [mm]	0.7*0.4		
PCB板孔径	PCB Hole Diameter [mm]	Ø1.0		

DES.	WuBW	DATE	24.06.14	UNITS	mm	THIRD ANGLE PROJECTION		
CHK.	HuHT	DATE	24.06.14	SIZE	A4	TYPE: CUSTOMER DRAWING	SHEET 1 of 1	
APP.	Jason	DATE	24.06.14	SCALE	3:1	DRAWING TYPE: SP-03	REV	VO
 慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						PART NO.: WJ211V-2.54-XXP-1Y-00A		