

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除单独给予明确授权，否则禁止转让、复制、利用、交流本文件的内容。侵犯者将负赔偿责任。本公司保留对涉及发明、实用新型和外观设计的所有权利。

1

2

3




4

5

6

REVISION RECORD

REV.	DESCRIPTION	ECN No.	APPROVED	DATE
V0	新发行		YuCZ	25.05.16



General Tolerances

variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 10	over 10 to 100	over 100 to 100
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30

UL/CUL 技术参数			UL1059		
UL/CUL	Technical Data				
等级	Use Group		B	C	D
额定电压	Rated Voltage [V]		600	600	/
额定电流	Rated Current [A]		20	20	/
接线范围	Wire Range		30-12		
单/多芯线	Solid/Stranded [AWG]				
耐电压	Withstanding Voltage		2200V/1Min		
IEC 技术参数			IEC61984		
IEC Technical Data					
过电压类别	Overvoltage Category		III	III	II
污染等级	Contamination Class		3	2	2
额定电压	Rated Voltage [V]		1000	1000	1000
额定电流	Rated Current [A]		16	16	16
额定冲击电压			8.0	8.0	6.0
Impulse withstand voltage	[KV]				
导线截面积	Conductor cross section		0.2-2.5		
硬质/柔性导线	Solid/ flexible [mm²]				
一般参数 Other Data					
间距 Pitch / 极数 Poles	[mm] / [P]		7.62 / 02~12		
剥线长度	Stripping Length [mm]		8		
螺丝 Screw/ 扭矩 Torque(Max)	[N.m]		M3/0.5		
工作温度	Operating temperature [°C]		-40~105		
符合RoHS环保要求					
5	Screw	Steel	M3/Zn Plated		
4	Cage	Copper Alloy	M3/Ni Plated		
3	Carrier	Copper Alloy	Sn Plated		
2	Cover	PA66	UL94V-0		
1	Housing	PA66	UL94V-0		
ITEM	NAME OF PART	MATERIAL	NOTES		

DES.	YuCZ	DATE	25.05.16	UNITS	mm	THIRD ANGLE PROJECTION	⊕
CHK.	YangHJ	DATE	25.05.16	SIZE	A4	TYPE: CUSTOMER DRAWING	SHEET 1 of 1
APP.	JASON	DATE	25.05.16	SCALE	2:1	DRAWING TYPE: SP-03	REV V0



慈溪市万捷电子有限公司
CIXI WANJIE ELECTRONIC CO., LTD

PART NO.:
WJ2KHR-7.62-XXP-1Y-00A