






Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权,否则禁止转让、复制、利用、交流本文档的内容。侵犯者将承担赔偿责任。侵权者将承担赔偿责任。



REVISION RECORD				
REV.	ESCRPTION	ECN No.	APPROVED	DATE
V0	新发行		WangZF	24.12.05

UL/CUL 技术参数				
UL/CUL Technical Data				
等级	Use Group	B	C	D
额定电压	Rated Voltage [V]	300	-	300
额定电流	Rated Current [A]	15	-	10
接线范围	Wire Range	28-12		
单/多芯线	Solid/Stranded [AWG]			
耐电压	Withstanding Voltage	1600V/1Min		
IEC 技术参数				
IEC Technical Data				
过电压类别	Overvoltage Category	III	III	II
污染等级	Contamination Class	3	2	2
额定电压	Rated Voltage [V]	320	320	630
额定电流	Rated Current [A]	16	16	16
额定冲击电压	Impulse withstand voltagea [KV]	4	4	4
导线截面积	Conductor cross section	0.25-2.5		
硬质/柔性导线	Solid/ flexible [mm²]			
材 料				
绝缘材料	Insulation Material			
阻燃等级	Imflammability			
导体材料	Contactior Material			
导体表面镀层	Contactive Coating			
一般参数				
间距	Pitch /极数 Poles [mm] / [P]			
工作温度	Operating temperatur [°C]			
剥线长度	Stripping Length [mm]			

General Tolerances

variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

5	Clamp	Copper Alloy	Sn Plated
4	Spring	Stainless steel	/
3	Cover	PA66	UL94V-0
2	Housing2	PA66	UL94V-0
1	Housing1	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

DES.	WangZF	DATE	24.12.05	UNITS	mm	THIRD ANGLE PROJECTION	
CHK.	HuHT	DATE	24.12.05	SIZE	A4	TYPE: CUSTOMER DRAWING	
APP.	Jason	DATE	24.12.05	SCALE	2:1	DRAWING TYPE: SP-03	
						PART NO.: WJ0501-04XX-1Y-00A	
慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						SHEET 1 of 1	
						REV	V0