

General Tolerances								—		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

UL/CUL 技术参数				
UL/CUL Technical Data				
等级	Use Group	B	C	D
额定电压	Rated Voltage [V]	300	-	300
额定电流	Rated Current [A]	15	-	10
接线范围	Wire Range	28-12		
单/多芯线	Solid/Stranded [AWG]			
耐电压	Withstanding Voltage	1600V		
IEC 技术参数		IEC 60664-1		
IEC Technical Data				
过电压类别	Overvoltage Category	III	III	II
污染等级	Contamination Class	3	2	2
额定电压	Rated Voltage [V]	320	320	630
额定电流	Rated Current [A]	12	12	12
额定冲击电压	Impulse withstand voltage [KV]	4	4	4
导线截面积	Conductor cross section	0.2-2.5		
硬质/柔性导线	Solid/flexible [mm²]			
一般参数 Other Data				
间距/极数	Pitch / Poles [mm] / [P]	5.0/ 02-24		
剥线长度	Stripping Length [mm]	7-8		
螺丝/扭矩	Screw/ Torque [N.m]	/		
工作温度	Operating temperature [°C]	-40~105		
符合RoHS环保要求				
5	Cover	PA66	UL94V-0	
4	Spring	Stainless steel		
3	Clamp	Copper Alloy	Sn Plated	
2	Housing 2	PA66	UL94V-0	
1	Housing 1	PA66	UL94V-0	
ITEM	NAME OF PART	MATERIAL	NOTES	

DES.	YuCZ	DATE	24.11.21	UNITS	mm	THIRD ANGLE PROJECTION	
CHK.	YangHJ	DATE	24.11.21	SIZE	A4	TYPE: CUSTOMER DRAWING	SHEET 1 of 1
APP.	JASON	DATE	24.11.21	SCALE	2:1	DRAWING TYPE: SP-03	REV V0
 慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						PART NO.: WJ0406-04XX-1Y-00A	