



Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权,否则禁止转让、复制、利用、交流本文档的内容。侵犯者将承担赔偿责任。侵权者将承担赔偿责任。



General Tolerances								—		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

4	Pin header	Copper Alloy	Sn Plated
3	Spring	Stainless steel	/
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

DES.	WangZF	DATE	24.12.05	UNITS	mm	THIRD ANGLE PROJECTION	
CHK.	HuHT	DATE	24.12.05	SIZE	A4	TYPE: CUSTOMER DRAWING	
APP.	Jason	DATE	24.12.05	SCALE	2:1	DRAWING TYPE: SP-03	
慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						PART NO.: WJ0103-01XX-1Y-00A	
WANJIE						REV V0	

REVISION RECORD					
REV.	ESCRPTION		ECN No.	APPROVED	DATE
V0	新发行			WangZF	24.12.05
	UL/CUL 技术 参数				
	UL/CUL Technical Data				
	等 级	Use Group	B	C	D
	额定电压	Rated Voltage [V]	150	-	150
	额定电流	Rated Current [A]	4	-	4
	接线范围	Wire Range	28-20		
	单/多芯线	Solid/Stranded [AWG]			
	耐电压	Withstanding Voltage	1300V/1Min		
	IEC 技术参数		IEC61984		
	IEC Technical Data				
	过电压类别	Overvoltage Category	III	III	II
	污染等级	Contamination Class	3	2	2
	额定电压	Rated Voltage [V]	100	160	320
	额定电流	Rated Current [A]	6	6	6
	额定冲击电压	Impulse withstand voltagea [KV]	2.5	2.5	2.5
	导线截面积	Conductor cross section	0.25-0.5		
	硬质/柔性导线	Solid/ flexible [mm²]			
	材 料		Material		
	绝缘材料	Insulation Material	PA66		
	阻燃等级	Imflammability	UL94V-0		
	导体材料	Contactor Material	铜合金 Copper alloy		
	导体表面镀层	Contactive Coating	镀锡 Sn Plated		
一般参数		Other Data			
间距	Pitch /极数 Poles [mm] / [P]	2.5 / 02~12			
工作温度	Operating temperatur [°C]	-40~105			
剥线长度	Stripping Length [mm]	5-6			

1 2 3 4 5 6