




Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除经许可外，复制或传播本文件内容，或在本文件内容基础上进行发明、实用新型和外观设计专利的所有权利。



电气性能/Electrical

额定电压/Rated voltage	300V
额定电流/Rated current	20A
接触电阻/Contact resistance	20mΩ
绝缘电阻/Insulation resistance	500MΩ/DC500V
使用线径/Wire range	22~12AWG
耐电压/Wrth standing voltage	AC 1600V/1 Min

机械性能/Mechanical

扭矩/Torque	0.8Nm(7.11Lb.in)
温度范围/Temp.Range	-40°C~+105°C
瞬时温度/MAX Soldering	+260°C, for 5 Sec

尺寸/Dimensions

间距/Pitch	9.5mm
极数/Poles	2~26p

3	current-carrying part	Copper Alloy	Ni Plated
2	Screws	Steel	M3.5Steel Ni plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

DES.	WuBW	DATE	24.10.08	UNITS	mm	THIRD ANGLE PROJECTION	
CHK.	HuHT	DATE	24.10.08	SIZE	A4	TYPE: CUSTOMER DRAWING	
APP.	Jason	DATE	24.10.08	SCALE	2:1	DRAWING TYPE: SP-03	
慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						PART NO.: WJ49M-XXP-1Y-00A	

General Tolerances

General Tolerances								—		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

1

2

3

4

5

FOR-0371 Rev.1.0