






慈溪市万捷电子有限公司

CIXI WANJIE ELECTRONIC CO., LTD

REVISION RECORD

REV.	DESCRIPTION	ECN No.	APPROVED	DATE



UL/CUL 技术参数 (UL1059)		UL/CUL Technical Data			
等 级	Use Group		B	C	
额定电压	Rated Voltage	[V]	600	600	
额定电流	Rated Current	[A]	60	60	
耐电压	Withstanding Voltage		2200V/1Min		
接线范围	Wire Range		20-6		
单/多芯线	Solid/Stranded	[AWG]			
IEC 技术参数 (IEC60947-7-1)					
IEC Technical Data					
过电压类别	Overvoltage Category		III		
污染等级	Contamination Class		3		
额定电压	Rated Voltage	[V]	1000		
额定电流	Rated Current	[A]	57		
额定冲击电压	Impulse withstand voltagea	[KV]	8		
导线截面积 Conductor cross section					
单芯	Solid	[mm²]	0.5-16		
柔性导线	flexible	[mm²]	0.5-10		
柔性导线带冷压头	flexible with ferrule	[mm²]	0.5-10		
材 料 Material					
绝缘材料	Insulation Material		PA66		
阻燃等级	Imflammability		UL94V-0		
导体材料	Contact Material		铜合金 Copper alloy		
导体表面镀层	Contactive Coating		镀锡 Sn Plated		
一般参数 Other Data					
连接点数	connection points		2		
剥线长度	Stripping Length	[mm]	18		
导轨类型	Type of rail		DIN 35		
螺丝 Screw/扭矩	Torque(Max)	[N.m]	--		
工作温度	Operating temperatur	[°C]	-40-105		

红色/Red	GUV10-102-RD-00A
黑色/Black	GUV10-102-BK-00A
黄色/Yellow	GUV10-102-YE-00A
绿色/Green	GUV10-102-GN-00A
橙色/Orange	GUV10-102-OG-00A
蓝色/Blue	GUV10-102-BU-00A
灰色/Gray	GUV10-102-GY-00A
颜色/Colour	订货号 /Order No.

linear dimension(Tolerances Standard GB/T 14486-2008)									
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30

单位 / UNITS	mm	尺寸 / SIZE	A4	比例 / SCALE	1:1	第三视角 / THIRD ANGLE PROJECTION	版本 / REV	V0
慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						名称 / TITLE	GUV10-102-XX-00A	