



慈溪市万捷电子有限公司
CIXI WANJIE ELECTRONIC CO., LTD

UL/CUL 技术参数 (UL1059)					UL logo				
UL/CUL Technical Data									
等级	Use Group	B	C	D					
额定电压	Rated Voltage	V	-	-					
耐电压	Withstanding Voltage	1600V/1min							
接线范围	Wire Range	26-14							
单芯芯线	Solid/Stranded	[AWG]							
IEC 技术参数 (IEC30947-7-2)									
IEC Technical Data									
过电压类别	Overvoltage Category	III							
污染等级	Contamination Class	3							
额定电压	Rated Voltage	V							
额定开断电压	Rated breaking voltage	[kV]							
脉冲 withstand voltage		6							
导线截面积 Conductor cross section									
单芯	Solid	[mm²]							
柔性导线	flexible	[mm²]							
柔性导线带冷压头	flexible with ferrule	[mm²]							
材料 Material									
绝缘材料	Insulation Material	PA66							
阻燃等级	Inflammability	UL 94V-0							
导体材料	Conductor Material	铜合金 Copper alloy							
导体表面镀层	Contactive Coating	镀锡 Sn Plated							
一般参数 Other Data									
连接点数	connection points	4							
接线长度	Shipping Length	[mm]							
导线类型	Type of rail	DIN 35							
螺丝 Screw/扭矩 Torque(Max)		[N.m]							
工作温度	Operating temperatur	[°C]							