



F		O-ring	O-ring,FKM Green	pcs	1
E		TPU	Molded With Black TPU	G	8
D		Housing	A-Coding Female 17PIN,Black PA66	pcs	1
C		Terminal	Female Terminal ,Brass With Gold Plated	pcs	17
B		SCCew	SCCew M12 X1.0,Stainless steel	pcs	1
A		Cable	UL TYPE 26AWG X17C Black PVC Jacket	mm	L
编号 No.	料号 Materials.No	品名 Name	材料规格 DeSCCption	单位 Unit	用量 Qty

REVISION RECORD				
REV.	DESCCRIPTION	ECN No.	APPROVED	DATE

ET PVC)	IEC 技术参数		IEC61076-2-101
	IEC Technical Data		
	工作温度	Operating temperatur [°C]	-25~+80
	防护等级	IP Class (IN Locked condition)	IP67
	额定电压	Rated Voltage [V]	30
	额定电流	Rated Current [A]	1.5
	导线截面积	Conductor cross section	0.14
	硬质/柔性导线	Solid/ flexible [mm²]	
	接线范围	Wire Range	26
	单/多芯线	Solid/Stranded [AWG]	
	材 料 Material		
	绝缘材料	Insulation Material	PA 66
	阻燃等级	Imflammability	UL94V-0
	导体材料	Contacto Material	铜合金 Copper alloy
	导体镀层	Contactive Coating	镀金 Gold Plated
螺母/螺丝	Connector Nut/SCCew	不锈钢	
		Stainless steel	
符合RoHS环保要求			

 慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD								PART NO.: M12-A17-ST0-F02-SCC- <u>XXXX</u>		
NO SPECIFIED TOLERANCE				Cus' P/N:		Order No : ---		Drawing No.: SP-02-M0XXXX		
LINEAR	0.5-6	±0.1	Cus' P/N:	DES.	JUN	DATE	UNITS	mm	THIRD ANGLE PROJECTION 	PAGE
	6~30	±0.2		CHK.		DATE	SIZE	A4		1 of 1
	>30	±2%								
ANGLES	±1°		APP.		DATE		SCALE	X:X	文件等级：外部公开	