


Contacts Pin 数	4Pin
A—Coding	
Rated Current 额定电流	4A
Rated Voltage 额定电压	250V
Wire Range线范围	22AWG
PART NO. 品名: (1M)	M12-A04-ST0-F02-SCR-100N
PART NO. 品名: (2M)	M12-A04-ST0-F02-SCR-200N
PART NO. 品名: (3M)	M12-A04-ST0-F02-SCR-300N
PART NO. 品名: (5M)	M12-A04-ST0-F02-SCR-500N
Customized. 定制化	

P1	Wirelist
1	brown
2	white
3	blue
4	black

F		O-ring	O-ring,FKM Green	pcs	1
E		TPU	Molded With Black TPU	G	8
D		Housing	A-Coding Female 4PIN,Black PA66	pcs	1
C		Terminal	Female Terminal ,Brass With Gold Plated	pcs	4
B		Screw	Screw M12 X1.0,Stainless steel	pcs	1
A		Cable	UL TYPE 22AWG X4C Black PUR Jacket	mm	L
编号 No.	料号 Materials.No	品名 Name	材料规格 DeScription	单位 Unit	用量 Qty

 慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD							PART NO.: M12-A04-ST0-F02-SCR- <u>XXXX</u>			
NO SPECIFIED TOLERANCE			Cus' P/N:		Order No :		Drawing No.:		SP-02-M0XXXX	
LINEAR	0.5~6	±0.1	DES.	JUN	DATE	UNITS	mm	THIRD ANGLE PROJECTION	PAGE	
	6~30	±0.2								
	>30	±2%								
			CHK.		DATE	SIZE	A4		1 of 1	
ANGLES	±1°		APP.		DATE	SCALE	X:X		文件等级:外部公开	