



Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除经给予明确授权, 否则禁止转让、复制、利用、交流本文件的内容。侵犯者将负赔偿责任。本公司保留对涉及发明、实用新型和外观设计专利的所有权利。



REVISION RECORD				
REV.	ESCRIPTION	ECN No.	APPROVED	DATE
V0	新发行		WangP	23.10.18

参考标准/ Standard	UL	IEC
额定电压/ Rated voltage	600V	750V
额定电流/ Rated current	30A	41A
接触电阻/ Contact resistance	20mΩ	
绝缘电阻/ Insulation resistance	500MΩ/DC500V	
使用线径/ Wire range	20~10AWG	6.0mm²
耐 电 压/ Wrth standing voltage	AC 2200V/1 Min	
机 械 性 能/ Mechanical		
扭矩/ Torque	0.8Nm(7.2Lb.in)	
温度范围/ Temp.Range	-40°C~+105°C	
剥线长度/ Steip Length	7-8mm	
尺 寸/ Dimensions		
间 距/ Pitch	12.0mm	
极 数/ Poles	2~12p	



DES.	WangP	DATE	23.10.18	UNITS	mm	THIRD ANGLE PROJECTION	☉
CHK.	YangHJ	DATE	23.10.18	SIZE	A4	TYPE: CUSTOMER DRAWING	SHEET 1 of 1
APP.	JASON	DATE	23.10.18	SCALE	2:1	DRAWING TYPE: SP-03	REV V0
慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						PART NO.: MY12HW-1.2-12.0-XXP-1Y-00A	