





Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除丰给予明确授权，否则禁止转让、复制、利用、交流本文件的内容。侵犯者将承担赔偿责任。侵犯者将承担赔偿责任。侵犯者将承担赔偿责任。



General Tolerances								—  ⊥		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
V0	新发行		YuCZ	23.11.27

UL/CUL 技术参数 UL/CUL Technical Data					
等 级	Use Group		B	C	D
额定电压	Rated Voltage	[V]	300	-	300
额定电流	Rated Current	[A]	15	-	10
接线范围	Wire Range		-		
单/多芯线	Solid/Stranded	[AWG]			
耐电压	Withstanding Voltage		1600V/1Min		
IEC 技术参数 IEC Technical Data			IEC61984		
过电压类别	Overvoltage Category		III	III	II
污染等级	Contamination Class		3	2	2
额定电压	Rated Voltage	[V]	250	320	400
额定电流	Rated Current	[A]	12	12	12
额定冲击电压	Impulse withstand voltage	[KV]	4.0	4.0	4.0
导线截面积	Conductor cross section		-		
硬质/柔性导线	Solid/ flexible	[mm²]			
一般参数 Other Data					
间距 Pitch / 极数	Poles	[mm] / [P]	5.0 / 2*02~2*24		
工作温度	Operating temperature	[°C]	-40~130		
焊接方式	Soldering method		Reflow Soldering		
符合RoHS环保要求					
2	Pin		Copper Alloy		Sn Plated
1	Housing		LCP		UL94V-0
ITEM	NAME OF PART		MATERIAL		NOTES

DES.	YuCZ	DATE	23.11.27	UNITS	mm	THIRD ANGLE PROJECTION			
CHK.	YangHJ	DATE	23.11.27	SIZE	A4	TYPE: CUSTOMER DRAWING		SHEET 1 of 1	
APP.	JASON	DATE	23.11.27	SCALE	2:1	DRAWING TYPE: SP-03		REV	V0
WANJIE 慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						PART NO.: WJ2EDGVHB-THR-5.0-2*XXP-1Y-00A			